


RELY ON EXCELLENCE

## BuraGlas GS tape 9495

Packings & Gaskets | Glass fiber seals & tapes



### Advantages

- High temperature stability
- High flexibility

### Operating range

#### Temperature

- Continuous operation:  
 $t_{\max} = +550\text{ °C}$
- transient peak temperature:  
 $t_{\max} = +650\text{ °C}$

#### Chemical resistance:

pH = 6 ... 10

### Recommended applications

#### Industries

- Power plant technology
- Building services engineering
- Metal production and processing

#### Components

- Furnace doors
- Ducts
- Metal crucibles

### Features

BuraGlas GS tape 9495 is woven glass fiber sealant tape made of multiple glass layers. The individual layers are stitched and glued together. If needed the sealing tape can be impregnated with a high temperature-resistant graphite compound. All products from the BuraGlas range are manufactured from materials and fibers that meet the safety requirements of the World Health Organization (WHO).

## RELY ON EXCELLENCE

### Dimensions

- Sold by length on rolls in 25, 50 or 150 m lengths
- Standard dimensions  
(Width x Height x Length):
  - 15 x 2 mm x 150 m
  - 20 x 2 mm x 150 m
  - 30 x 2 mm x 50 m
  - 40 x 2 mm x 50 m
  - 50 x 2 mm x 50 m
  - 60 x 2 mm x 50 m
  - 80 x 2 mm x 50 m
  - 100 x 2 mm x 50 m
  - 10 x 3 mm x 150 m
  - 15 x 3 mm x 150 m
  - 20 x 3 mm x 150 m
  - 30 x 3 mm x 50 m
  - 40 x 3 mm x 50 m
  - 50 x 3 mm x 50 m
  - 80 x 3 mm x 50 m
  - 100 x 3 mm x 50 m
  - 20 x 4-5 mm x 20 m
  - 30 x 4-5 mm x 20 m
  - 40 x 4-5 mm x 20 m
  - 50 x 4-5 mm x 20 m
  - 100 x 4-5 mm x 20 m