

RELY ON EXCELLENCE

Rotatherm Tape 0902

Packings & Gaskets | Packings for valves



Features

Rotatherm tape 0902 is nuclear grade pure graphite tape (purity $\geq 99.85\%$). It is suitable for sealing or packing valve spindles during servicing. They are used to quickly and easily create working packing rings inside the valve.

Advantages

- Do not harden
- Long service life
- Uncomplicated installation and removal

Operating range

Temperature

- Continuous operation:
 $t = -200\text{ °C} \dots +500\text{ °C}$

Chemical resistance:

pH = 0 ... 14

Resistant to almost all organic and inorganic acids, alkalis, oils and solvents.

Standards and approvals

- BAM (upon request)

Article numbers of variants

0902/10 (10 mm wide)
0902/15 (15 mm wide)
0902/20 (20 mm wide)
0902/25 (25 mm wide)
0903: knurled, self-adhesive

Forms of supply

- Sold by length on rolls in boxes in 12 and 15 m lengths
- Standard dimensions:
(Width x Height)
10 x 0.5 mm
15 x 0.5 mm
20 x 0.5 mm
25 x 0.5 mm
30 x 0.5 mm

Recommended applications

- Chemical industry
 - Petrochemical industry
 - Oil & gas industry
 - Process industry
 - Pharmaceutical industry
 - Power plant technology
 - Building services engineering
- Components
- Valves